

Data Sheet TM Series

TM Liquid In-Line Turbine Flow Meter

Highly Accurate and Reliable Liquid Flow Metering

urbines, Inc. is a leader in the design and manufacture of reliable and accurate turbine flow metering equipment, electronic monitors, and accessories. All of our products are engineered, manufactured, and calibrated using premium quality materials by a skilled engineering team, using state-ofthe-art equipment.

The **TM Series Liquid Turbine** flow meter is a highlyversatile product line that offers all stainless steel, precision-machined components with CD4MCu and/or 416 steel rotors. Available for flow ranges from 3/8" to 10", Turbines Inc.'s TM Series meters can handle line sizes as small as 1/2" and up to 10". The TM Series is designed specifically for liquid applications and can be configured with a variety of end arrangements, including threaded, flanged, grooved, or any other means as specified.

The TM Series provides +/- 1.0% standard accuracy, and is repeatable to +/- 0.10% over the entire flow range. For every turbine flow meter manufactured by Turbines, Inc., a unique K-factor is established by means of a NIST-traceable factory calibration.

Specifications

| Performance Data | | | | | | | |
|------------------------|---|--|--|--|--|--|--|
| Accuracy | +/- 1.0% over flow range (except TM0038 which is +/- 2.0%) | | | | | | |
| Repeatability | +/- 0.1% over flow range | | | | | | |
| Operating Temperature | -100° F to +300° F | | | | | | |
| Connection | Flanged, Victaulic [®] (grooved), or threaded | | | | | | |
| Materials | | | | | | | |
| Meter Body | 316 stainless steel | | | | | | |
| Rotor Supports | 316 stainless steel | | | | | | |
| Meter Rotor | CD4MCu/416 stainless steel | | | | | | |
| Rotor Shaft | Tungsten carbide | | | | | | |
| Sleeve Bearings | Tungsten carbide | | | | | | |
| Certifications | ISO 9001 | | | | | | |
| Additional Information | Full line of economical Retrofit Kits are available Factory refurbishment with one (1) day turnaround is available | | | | | | |

ISO 9001 | AS 9100 | Canadian CRN Certified

Data Sheet TM Series

| Turbines Part Number | End Connection Size (in) | Flow Range (GPM) | Flow Range (BPD) | Flow Range (M3PD) | Flow Range (LPM) | Max Pressure (PSI) | Repair Kits (Kits come with: 2-Rotor Supports, 1-Rotor, & 2-Retaining Rings) |
|-------------------------|---|---------------------|---------------------|----------------------|---------------------|--------------------------|---|
| TM0038 TM0038X 1/2 | 1" X 1" Male NPT 1/2" X 1/2" Male NPT | 0.3 - 3 | 10 - 100 | 1.6 - 16 | 1.14 - 11.36 | 5,000 | TK0038 |
| TM0050 TM0050X 1/2 | 1" X 1" Male NPT ½" X ½" Male NPT | 0.75 - 7.5 | 25 - 250 | 4 - 40 | 2.84 - 28.39 | 5,000 | TK0050 |
| TM0075 TM0075X 1/2 | 1" X 1" Male NPT ½" X ½" Male NPT | 2 - 15 | 68 - 514 | 11 - 80 | 7.57 - 56.78 | 5,000 | TK0075 |
| TM0078 TM0078-VIC | 1" X 1" Male NPT 1" X 1" Victaulic | 3 - 30 | 102 - 1,028 | 16 - 160 | 11.36 - 113.6 | 5,000 800 | TK0078 |
| TM0100 TM0100-VIC | 1" X 1" Male NPT 1" X 1" Victaulic | 5 - 50 | 170 - 1,714 | 27 - 270 | 18.93 - 189.3 | 5,000 800 | TK0100 |
| TM0150 TM0150-VIC | 1½" X 1½" Male NPT 1½" X 1½" Victaulic | 15 - 180 | 514 - 6,000 | 80 - 980 | 56.8 - 681.35 | 5,000 800 | TK0150 |
| TM0200L TM200L-VIC | 2" X 2" Low Flow Male NPT 2" X 2" Low Flow Victaulic | 15 - 180 | 514 - 6,000 | 80 - 980 | 56.8 - 681.35 | 5,000 800 | TK0150 |
| TM0200 TM0200-VIC | 2" X 2" Female NPT 2 ½" X 2 ½" Victaulic | 40 - 400 | 1,371 - 13,714 | 218 - 2,180 | 151 - 1,514 | 5,000 800 | TK0200 |
| ТМ0300 | 3" Victaulic | 60 - 600 | 2,100 - 21,000 | 320 - 3,200 | 227 - 2,270 | 800 | TK0300 |
| TM0400 | 4" Victaulic | 120 - 1,200 | 4,100 - 41,000 | 654 - 6,541 | 454 - 4,542 | 800 | TK0400 |
| ТМ0600 | 6" Victaulic | 250 - 2,500 | 8,571 - 85,710 | 1,362 - 13,627 | 946 - 9,463 | 800 | TK0600 |
| TM0800 | 8" Victaulic | 350 - 3,500 | 12,000 - 120,000 | 1,907 - 19,080 | 1,324 - 13,248 | 800 | TK0800 |
| ТМ1000 | 10" Victaulic | 550 - 5,500 | 19,000 - 190,000 | 2,998 - 29,980 | 2,081 - 20,819 | 800 | TK1000 |

Performance Specifications

Magnetic pick up is standard on all models (no extra charge).

Support and Service

Our full-time, dedicated service group offers 100% trustworthy support and recertification for flow meters — whether our own or a competitor's brand. Our meter proving services are performed by our trained technicians and the latest testing equipment.

Custom meters and instrumentation options for your application are readily available. Our products are always in stock and ready for immediate shipment, typically within 24 hours.

Certifications

Turbines, Inc.'s quality management systems are ISO 9001 and AS 9100 compliant and Canadian CRN certified.

Worldwide Support

Turbines, Inc. derved customers worldwide with U.S. offices in Cranston, RI (headquarters); Houston and Odessa-Midland, TX; Tulsa and Altus, OK; Seneca, SC; as well as locations in Edmonton, Alberta (Canada) and Beijing, China.

Contact your Turbines, Inc. Field Application Engineer for assistance.



P.O. Box 933 | 15935 U.S. Highway 283 | Altus, OK 73522 USA Tel: +1-800-809-1387 | Fax: +1-580-477-3071

www.turbinesincorporated.com

Turbines, Inc. products and operations are certified to industry standards for safety and performance. Visit our web site for details.



All Turbines, Inc. products are proudly made in the U.S.A.